

INDUSTRIAL PORTABLE SMAW WELDER

DISCOVER 200DX

SMAW/ARC Welding



TECHNICAL SPECIFICATION

Input Specifications

Input Supply: 165-280VAC, 1Ph, 50/60Hz Input @ 200A / 28V: 6.9KVA / 8.8HP, 30.1A@220V Input @ 141A / 26V: 5.0KVA / 5.7HP, 20.5A@220V

Output Specifications

Output Current Range: 10A to 200A Duty Cycle @ 50%: 200A / 28V

Duty Cycle @ 100%: 141A / 26V

Open Circuit Voltage (OCV): 75V-95V DC

Mechanical Specifications

Dimensions (LxWxH): 390x140x280mm Weight: 8kg

Protection Features

OT-Over Temperature

(when internal temperature more than 70°C).

OC-Over Current

(when over current flows through IGBT).

IP65 Panel parts dust and water protected front panel switches & buttons.

IP21 Rated chassis suitable for outdoor as well as indoor use.

Steel Body for long life and rugged usage.

Terminals Lug type heavy duty rated.



- 1. CURRENT SETTING
- 2. CURRENT DISPLAY
- 3. POSITIVE TERMINAL
- **4. NEGATIVE TERMINAL**



A) Discover 200DX power source

■ Order Code : APS - D200DX



1) Electrode Holder 200A with 2 meter 16sqmm cable



2) Earthing Clamp 200A with 2 meter 16sqmm cable









