



HIGH FREQUENCY UNIT

APS provides the External High Frequency Unit for TIG welding. These unit are light in weight and portable. They can be used arc welder or power sources which provide scratch start TIG mechanism. It adds up all the advantages of a High Frequency powered TIG welding equipment. It also has pre-flow and post-flow time adjustment knobs to achieve better quality weld joints.

- **Switch** - TIG Switch
- **Variable Parameters** - Preflow
Postflow
- **Compatibility** - 400A
600A
- **Dimension (W X L X H)** - 332 X 325 X 215 in mm
- **Weight** - 10 Kg



Copper Welding Cables

Size Sqmm	Current Capacity (A)	Configuration
16	120	509/0.2
25	160	796/0.2
35	230	1115/0.2
50	400	703/0.3
70	600	999/0.3
95	700	1346/0.3
120	1100	1699/0.3



All pictures shown are for illustrative purposes only.
All specifications in this document are for informational purposes only and are subject to change without prior notice.

AUTHORISED DEALER

ADVANCED POWER SOURCES[®] LIMITED

WELDING - CUTTING - GOUGING - AUTOMATION - ACCESSORIES

Registered Office:
No. 306, Sagar Industrial Estate, Near Toll Naka, Dahisar(E),
Mumbai, Maharashtra - 400 068. INDIA. Ph: 022-28967134
CIN: U74990MH2009PLC195896

Manufacturing Facility:
Survey no. 172/1, Paikee 2, Old GIDC, Gundlav, Valsad,
Gujarat - 396035 .INDIA. Ph: 02632-236799/98
email: info@apsl.in www.apsl.in